

Flowlok CS

PRIMER

Description

FLOWLOK CS primer is a fast curing, liquid applied, epoxy-polyamine primer with unique penetrating characteristics to lock in rising moisture. FLOWLOK CS has excellent adhesion to wood, concrete and metal substrates and can be used in low temperature applications. Not only is this designed for the FLOWLOK PLRM roofing and traffic coatings assemblies but can also be used as a moisture barrier floor sealer, as well.

Application

Prior to application, refer to install guide and recommendations for complete application instructions. Applicator is responsible for ensuring conditions are appropriate to proceed with proper application method.

Product Uses

- Concrete
- Plywood
- Polyurethane Elastomeric surfaces
- Metal

Charachteristics / Advantages

- Easy install
- Excellent Adhesion
- Rapid Cure

Physical / Liquid Properties

PERFORMANCE & PHYSICAL PROPERTIES	VALUE
Coverage Rate	1 GAL / 300 SF
Pot life, 75° F @ 50% R.H.	20 Min.
Dry film thickness per coat	5 mils
Specific Gravity Part A	1.16
Specific Gravity Part B	1.03
Total Solids by Volume	100%
Viscosity at 80° F (Part A & B combined)	600 + 200
VOC	0 lbs/ gal

CONTACT:

info@flowlok.com

Exclusive distribution and authorized installation in Northeastern United States by DripDrop Waterproofing



www.flowlok.com

BESSERN Building Products
 1400 North Providence Road, Media PA 19063
 Tel: 484-234-5035 • Fax: 484-234-5037